

Distribution and light construction

RENAULT TRUCKS D / D WIDE / C 2.3



Take the road with Renault Trucks

Driving with Renault Trucks means choosing a partner committed to supporting you, whenever you need it.

It means being able to select the most effective and technical solution. It means being able to choose trucks that are functional, efficient and comfortable.

It also means choosing easy to use, tried and tested technologies that are right for your business.

It involves building a strong, warm and lasting partnership.

It means making the right choice.





REDUCED CONSUMPTION INCREASED PRODUCTIVITY NEW TECHNOLOGY FOR FUEL SAVING SAVE MORE FUEL CHOOSE THE RIGHT BODY STRUCTURE FOR YOUR APPLICATION	P 04 P 06 P 08 P 10
TRUCKS DESIGNED FOR ALL ENVIRONMENTS A ROBUST TRUCK GETS AROUND IN TOWN ALWAYS AT YOUR SIDE SAVE MORE FUEL	P 12 P 14 P 16 P 18 P 20
INCREASED COMFORT FOR GREATER EFFICIENCY EVERYTHING WITHIN REACH ONBOARD COMFORT THE PERFECT TOOL FOR YOUR BUSINESS	P 22 P 24 P 26 P 28
SAFETY AS A PRIORITY OPTIMUM VISIBILITY WHATEVER THE WEATHER TECHNOLOGY THAT DELIVERS SAFETY	P 30 P 32 P 34
TECHNICAL SPECIFICATIONS RANGE POSTER DRIVELINE CHASSIS CAB BRAKES CUSTOMISATION PACKS	P 36 P 38 P 39 P 41 P 42 P 44 P 45 P 46

Reduced consumption increased productivity

When you choose Renault Trucks, you are purchasing much more than just a truck. With some exceptional body structural options available, you can be sure of working with a vehicle that is perfectly suited to your needs. And with better controlled improved fuel consumption, you can also rely on maximum profitability and even greater productivity.





New technology for fuel savings

Electric, natural gas, biodiesel or conventional diesel engines, Renault Trucks can help you choose the most suitable solution for your business.

Renault Trucks E-TECH D & D WIDE: zero emissions when operating



- → Fully charges overnight on AC power or under t wo hours on fast charge.
- Quiet and comfortable to drive.
- → Adapted driving range: between 200 kWh and 565 kWh, depending on configuration.

Renault Trucks D WIDE CNG up to 70% less CO₂* emissions

NATURAL GAS ENGINE

320 hp (NGT 9) for driving in areas where access is controlled and restricted to clean vehicles. Compatible with bio-methane.







OPTIDRIVER AND OPTISHIFT GEARBOXES

resulting in fuel savings compared to a manual gearbox.

Automated manual transmission as standard on D WIDE AND C 2.3*

→ DTI 5 and DTI 8 bio-diesel engines compatible with fuel types B30 and B100.



11-LITRE ENGINE (DE11) WITH A POWER RATING OF UP TO 460 HP

adapted for distribution and light construction applications.

Automatic gearbox as standard on D**



4-CYLINDER ENGINE (DTI 5) available in 210 hp and 240 hp.

Reduction of up to -10% in fuel consumption and CO₂ emissions with the DE11 engine and pack fuel ECO+

DE11 ENGINE

1 Improved combustion

2 Reduced friction losses

6 CYLINDER (DTI 8) ENGINE

available in 250 hp, 280 hp and 320 hp.



^{*} Automatic gearbox on CNG. ** option on D 4x4.

Save more fuel

By combining intelligent technologies, aerodynamic design and training in rational driving, the D Optifuel series are designed to significantly reduce your fuel consumption and thereby contribute to your profitability.



Automatic engine stop

to stop the engine running unnecessarily.



FUEL ECO eco mode (without kick down)

to avoid excessive fuel consumption.



Cruise control

combined with the Optiroll function to reduce fuel consumption further by benefiting from vehicle inertia.



FUEL ECO gearshift

changes gearshift strategy to reduce fuel consumption.

Geolocate your vehicle at any time OPTIFLEET



Roof deflector

adjustable with 12 different positions suitable for all body heights and all cabs.

Side deflectors

to reduce fuel consumption even further.



Choose the right body structure for your application

Many items of mechanical and electrical pre-equipment simplify bodymounting operations, allowing equipment for all distribution activities to be installed more easily. A web portal dedicated to bodybuilders reduces your vehicle delivery lead time.

A vehicle for every activity with a range of 100 models



POWER TAKE-OFF on gearbox and engine rear power take-offs adapted to suit all applications.



Switches on the dashboard for operating bodybuilder equipment



Flat cab roof for transporting cars



OVERALL HEIGHT FROM 2,690 MM


to use the maximum amount of free space above the cab.

- 5 Front axle rating up to 9 tonnes
- 6 Plates and mounting brackets provided on the chassis
- 7 Rear axle rating up to 9 tonnes



VERTICAL EXHAUST

for body structures on refuse collection vehicles, sewer and drain cleaners and road sweepers.



A CHASSIS PRE-EQUIPPED FOR EACH APPLICATION

complete with nuts and bolts and predrilled side members plus specific equipment (tankers, sweepers, domestic waste collection tippers and firefighting).





PLATES AND MOUNTING BRACKETS ON SIDE MEMBERS

for easier body mounting.

→ Rear overhang with mounting holes every 55 mm






A robust truck

The chassis on the D range of vehicles has been tested under extreme load conditions. To guarantee reliability and maximum durability, the cab has been reinforced using equipment and materials acknowledged for their strength.

- 1 Cab subjected to impact tests and equipped with reinforced seats
- 2 Robust chassis suspensions suited to every application
- 3 Side members drilled according to vehicle configuration, guaranteeing the minimum number of holes and better structural resistance
- 4 Maintenance-free rear suspensions





PLASTIC BUMPER (D WIDE) WITH STEEL CORNER PIECES available as standard.



PLASTIC BUMPER (C 2.3) WITH STEEL CORNER PIECES

for greater resilience.



CHASSIS SIDE MEMBERS

in high tensile steel.



PLASTIC BUMPER (D)
WITH STEEL CORNER PIECES
available as standard.



ALL STEEL BUMPER (D) for intensive use.




AIR SUSPENDED REAR CHASSIS

offering increased stability and better protection of goods.

Gets around in town

With its reduced turning circle, small front overhang and compact cab, the specifications of the D range mean you can get around in town where every centimetre counts, and easily access the most congested urban areas.




Reduced turning circle for easier manoeuvring





→ REDUCED CAB WIDTH for improved handling.

Maximum torque from 900 rpm for a better response



DTI 8 - 250 HP

Always at your side

Renault Trucks supports you throughout your vehicle's service life to guarantee maximum uptime of your vehicle to ensure that your business keeps moving.



Quality parts and reliable service for peace of mind at work



Years extended warranty covering parts and labour.


2-year parts, breakdown and towing warranty for all operations carried out at an approved Renault Trucks repairer.

Original parts package

Quality original parts: reliable, strong and approved to maintain vehicle performance.

Exchange package

Reconditioned parts available to maintain your vehicle performance by giving them a second life.





24/7 breakdown service

With a network of experts capable of responding to your needs in 16 languages, a coordinator will be your exclusive point of contact for any work that has to be done. Breakdowns are dealt with by specially trained roadside technicians who use special vehicles and work with dedicated diagnostic tools.

Save more fuel

We can provide close monitoring of your fuel consumption and an eco-driving support.



→ OPTIFLEET CHECK*,


provides a clear view of vehicle energy consumption.

→ ECOSCORE**

included in the offer, get drivers'performance reports and support them on eco-driving.



- → Reduce your fuel consumption and CO₂ levels and emissions
- → Save money



^{*} Contact your dealer for more details.

^{**} for combustion vehicles only.






→ WITH OPTIFLEET MAP*,

optimise your deliveries and monitor your drivers' speed, fuel levels, identity and driving time in real time. With specific truck routes, you will save on unnecessary mileage.





- → Optimise your deliveries
- → Improve your service quality
- → Increase your efficiency and customer satisfaction





Everything within reach



- 1 Retarder control
- 2 Large 4.3" Digital display
- 3 Cruise control/speed limiter
- Adaptive Cruise Control (ACC)
- DAB MP3 bluetooth® radio with USB port and jack socket
- 6 Automated gearbox control

- 7 Leather steering wheel
- 8 Smartphone stand
- 7 Tablet stand



Onboard comfort

New seats have been developed to improve comfort. Thanks to the numerous storage compartments and equipment, everything you need to do your job is within easy reach.

10 types of cab for all applications



TABLET STAND including 2 USB-C ports.



CREW CAB VERSION for carrying up to 7 people.



STORAGE SPACE on the overhead console.



HEATED PNEUMATIC SEATS with adjustable side and lumbar supports.



CENTRAL STORAGE COMPARTMENT capacity 15 l, writing surface, bottle holder, cupholder and supplementary 24 V power supply.



STORAGE UNDER THE BENCH SEAT thanks to the lifting seat cushion.

The perfect tool for your business

Cab and windscreen accessibility has been designed to make the driver's day-to-day work easier and facilitate vehicle servicing.

- 1 Handles for easy access to the windscreen
- 2 Two steps built into the plastic bumper for windscreen access (additional step available on certain models)
- 3 Illuminated step
- 4 Low chassis height: from 804 mm

Easy cab access with 2 steps across the entire range





WINDSCREEN ACCESS STEPS

non-slip to make vehicle maintenance easier.



STAIRCASE TYPE STEPWELL

with an 80 mm recess between the two steps for easier cab access.



CHASSIS-MOUNTED

tool box.






90° OPENING

for easier cab access.

Quick access for checking levels



Safety as a priority

A truck should guarantee not only the safety of its driver, but also that of other road users. Renault Trucks D, D Wide and C 2.3 are equipped with every technological feature to avoid dangerous situations.





Optimum visibility whatever the weather

Glazed door sills, panoramic windscreen, two-part rear view mirrors and a cab rear window provide considerable improvements in terms of visibility. Our lighting options guarantee maximum safety under all conditions and in all environments.

Vision door for improved side visibility

→ VISION DOOR

available on the passenger side to improve visibility in urban areas. Optional glass side panels.





CAMERA

for the lane departure warning system and automatic emergency braking system.



CAB REAR WINDOW

to assist with handling equipment (tipper, platform).



DE-ICING AND ELECTRICALLY ADJUSTED REAR-VIEW MIRRORS

suitable for different cab widths with reinforced brackets (reduced vibration).



NEW LIGHTS

equipped with 4 LED daytime running lights.



LEDTail lights.



RADAR DETECTION

for the automatic emergency braking system.

Technology that delivers safety

Various powerful braking systems and retarders provide effective protection for both crew and load. We also offer additional equipment and accessories to further enhance driver safety.



RETARDER CONTROL

within easy reach behind the steering wheel.

- → Brake pad wear monitoring
- → EBS (electrically-controlled braking) and ASR (traction control)



DISC BRAKES

provide emergency braking deceleration of 7 m/s2 (the norm is 4.5 m/s2).

- → Exhaust brake as standard
- → Engine brake up to 300 kW without any increase in weight



RARETARDER


electric on drive train or hydraulic on gearbox*.

* Depending on model



ADAPTIVE CRUISE CONTROL (ACC)

keeps a safe distance from the vehicle in front by automatically adjusting the throttle and brake (retarders and service brakes).



HILL START AID

Assistance with hill starts. The brakes are held on for a few seconds after releasing the brake pedal for easier hill starts.



ELECTRONIC STABILITY CONTROL

as standard to help the driver to retain control of directional stability and prevent vehicle rollover in critical situations.

AUTOMATIC EMERGENCY BRAKING SYSTEM

possible collision warning followed by braking to bring the vehicle to a complete standstill without the driver's intervention.



LANE DEPARTURE WARNING SYSTEM

warns the driver with an audible alarm if an unintended deviation of the vehicle's direction is detected.

Technical specifications

Renault Trucks D

- 1 Three part bumper reduces maintenance costs
- 2 Checking levels
- 3 Offers wheelbases up to 6500 mm
- Camera for the lane departure warning system and automatic emergency braking system
- 5 3 chassis heights provided with wheel sizes 17.5" to 22.5"
- 6 Easy cab access via two steps
- Vision door available on both doors to improve visibility
- 8 Radar for AEBS and ACC

Renault Trucks D Wide

- 1 Three part bumper reduces maintenance costs
- 2 Checking levels
- 3 Lights equipped with integrated daytime running lights
- 4 Offers wheelbases up to 6800 mm
- 5 Camera for the lane departure warning system and automatic emergency braking system
- Low-level chassis available for high-volume versions
- 7 Easy cab access via two steps
- 8 Vision door available on both doors to improve visibility
- 9 Radar for AEBS and ACC

Renault Trucks C 2.3

- 1 Three part bumper reduces maintenance costs
- 2 Checking levels
- 3 Lights equipped with integrated daytime running lights
- 4 Offers wheelbases up to 6800 mm
- 5 Camera for the lane departure warning system and automatic emergency braking system
- 6 Low-level chassis available for high-volume versions
- 7 Easy cab access via two steps
- 8 Vision door available on both doors to improve visibility
- 9 Radar for AEBS and ACC



Range poster

Cab	Туре	Profile	GVW	GCW	Chassis	Engine	Power ratings	Gearbox	Drive axle	
			7,5 t	11 t-17,5 t	LOW					
		4x2	10 t	13,5-19 t	wheels	DTI 5	210 hp 240 hp		P08120	
			12 t	15,5-19 t	17,5"		240 Hp	6 speed Manual 8 speed Automatic		
			12 t	15,5-36 t		DTI 5	210 hp	o speca natomatic		
			13 t	16,5-36 t	MEDIUM	——————————————————————————————————————	240 hp		- P11140	
		4x2	14 t	17,5-36 t	wheels		250 hp	6 speed Manual	P11150	
			15 t	18,5 t	19,5"	DTI 8	280 hp	9 speed Manual 6 speed Automatic	P1191	
			16 t	19,5-36 t			320 hp	8 speed Automatic		
Renault Trucks	D:=:J		13 t	16,5-36 t		DTI 5	210 hp 240 hp	6 speed Manual 6 speed Automatic	- P11140	
D 2.1m Cab	Rigid		14 t	17,5-36 t			250 hp	6 speed Manual	P11150	
Cab		4x2	16 t	19,5-36 t		DTI 8	280 hp 320 hp	9 speed Manual 6 speed Automatic 8 speed Automatic	P1191	
		18 t 21,5-36 t	DTI 8	250 hp DTI 8 280 hp	6 speed Manual 9 speed Manual	P11150				
			19 t	21,5-36 t		DITO	320 hp*	6 speed Automatic 8 speed Automatic	F11130	
			12 t	16,5-25 t	HIGH		250 hp		PA611	
		4x4	14 t	17,5-25 t	wheels	DTI 8	280 hp	6 speed Manual 8 speed Automatic	FRONT	
			16 t	19,5-25 t	22,5"		320 hp		P1191 REAR	
			16 t	30 t 32 t 36 t			25 Ohp	12 speed Automated		
Renault	Rigid	4x2	18-19 t	30/32 t 36/40 t 44 t 50 t (With DE11)		DTI 8	280 hp 320 hp	6 speed Manual 9 speed Manual 6 speed Automatic	P13170 P13170-E P1361	
Trucks D Wide 2.3m		6x2 - 6x2*4	26 t	44 t 50 t	HIGH wheels 22,5"	DE11	380 hp 430 hp 460 hp	12 speed Automated		
Cab			16 t	32 t 36 t		DTI 8	280 hp 320 hp	12 speed Automated 9 speed Manual	P13170	
	Tractor	4x2		44 t		DTI 8	280 hp 320 hp	12 speed Automated 9 speed Manual	P13170-E	
			18-19 t	50 t (With DE11)		DE11	380 hp 430 hp 460 hp	12 speed Automated	P13170 P13170-E P1361	

^{*}Renault Trucks D DTI 8 320 hp only available with 8 speed Automatic gearbox

D WIDE CNG

Renault Trucks D Wide CNG 2.3m Cab	Rigid	4x2 6x2	18-19 t	22,5t 	HIGH wheels 22,5"	NGT 9	320 hp	6 speed Automatic	
C 2.3									
		4x2	18-19 t	32 t 40 t 44 t 50 t		DTI 8	250 hp 280 hp 320 hp	12 speed Automated 6 speed Manual 9 speed Manual 6 speed Automatic	P13170 P13170-E
Renault Trucks C 2.3m	Rigid	6x2 - 6x2*4 (TAG)	26 t	32 t 40 t 44 t 50 t	HIGH wheels	DE11	380 hp 430 hp 460 hp	12 speed Automated	P1361
Cab		6x4	26 t	40 t 44 t	22,5"	DTI 8	280 hp 320 hp	12 speed Automated 6 speed Manual 9 speed Manual	PMR 21150 PMR 23150 PMR 2161D PMR 2161E
	Tractor	4x2	18-19 t	40 t 44 t 50 t		DE11	380 hp 430 hp 460 hp	12 speed Automated	P13170 P13170-E P1361


Driveline

DIESEL ENGINES

DTI 5 EURO 6 ENGINE

Compatible with bio-diesel (240 hp) and XTL 154 kW (210 hp) – 800 Nm 176 kW (240 hp) – 900 Nm

Displacement	5.1 l
Cylinders	4 in line
Distribution	Rear
Bore	110 mm
Stroke	135 mm
Weight (including oil)	564 kg




DTI 8 EURO 6 ENGINE

Compatible with bio-diesel (320 hp) and XTL 184 kW (250 hp) – 950 Nm 206 kW (280 hp) – 1050 Nm 235 kW (320 hp) – 1200 Nm

Displacement	7.7 l
Cylinders	6 in line
Distribution	Rear
Bore	110 mm
Stroke	135 mm
Weight (including oil)	732 kg

DTI 8 - 280 HP





DE11 EURO 6 ENGINE

XTL compatible

285 kW (380 hp) – 1800 Nm 323 kW (430 hp) – 2050 Nm 344 kW (460 hp) – 2200 Nm

Displacement	10.8 l
Cylinders	6 in line
Distribution	Rear
Bore	123 mm
Stroke	152 mm
Weight (including oil)	965 kg





To respect the Euro 6 standard concerning polluting emissions, Renault Trucks D vehicles are fitted with an SCR system :

- → EGR : Cooled Exhaust Gas Recirculation
- Exhaust gas heating system with a dedicated injector (except DE11)
- → DOC: Diesel Oxidation Catalyst
- → DPF: Diesel Particulate Filter
- → SCR: Selective Catalytic Reduction (with injection of AdBlue®)

COMPRESSED NATURAL GAS (CNG)

NGT 9 CNG ENGINE

239 kW (320 hp) - 1356 Nm

Displacement
Cylinders
Distribution
Bore
Stroke
Weight (including oil)

8.9 l	1400
6 in line	1200 - 220
Rear	1100
114 mm	500
144.5 mm	800 - 140
777 kg	Nm 1000 12000 1400 1600 2000 kW
	NGT 9 - 320 HP

To comply with the Euro 6 polluting emissions standard, the D Wide CNG vehicle has the following main components:

→ EGR: Cooled Exhaust Gas Recirculation

three-way catalytic converter without an AdBlue® injection system or regeneration

GEARBOXES

3 manual gearboxes

3		ZF 6S800	ZF 6S1000	ZF 9S 1110 TO
Ni. mak an af maana	Forward	6	6	9
Number of gears	Reverse	1	1	1
Maximum torque		850 Nm	1050 Nm	1200 Nm

Two 12 speed automated manual gearboxes

Optidriver		AT 2412	ATO 2612
Number of some	Forward	12	12
Number of gears	Reverse	3	3
Maximum torque		2400 Nm	2550 Nm

2 automatic gearboxes

Allison		3200	
Number of goors	Forward	6	
Number of gears	Reverse	1	
Maximum torque		1491 Nm	
Ontichift		7E 0AD	
Optishift		ZF 8AP	
	Forward	ZF 8AP 8	
Optishift Number of gears	Forward Reverse		

DRIVE AXLES

		2.1 m Cab			2.3 m C	ab			
		4x2 rigid	4x4 rigid		4x2 rigi	id 4x2	rigid	6x2 rigid	6x4 rigid
	P08120	-							
	P11140								
	P11150								
Solo drive axle	P1191								
axie	P13170								
	P1391								
	P1361					•			
		Solo drive a	axle						
		Without redu	ıction				With red	uction	
		P08120	P11140	P1115	i0	P13170	P1191	P1391	P1361
	Axle torque	800 Nm	1050 Nm	1050	Nm	2600 Nm	1280 Nm	1200 Nm	3100 Nm
Capacities	Load per axle	8.5 t	11 t	11 t		13 t	11 t	13 t	13 t
	Max GCW	19 t	25 t	32,5 t		44 t	40 t	40 t	70 t

RETARDERS

	Engine	Retarding power
	DTI 5	80 kW
Exhaust brake	DTI 8	120 kW
	DE11	170 kW
Optibrake	DTI 8	170 kW
орны аке	DE11	300 kW
	DTI 5	370 kW
Electric	DTI 5/DTI 8	480 kW
	DTI 8	620 kW
Hydraulic (Allison)	DTI 8/NGT 9	400 kW
Hydraulic (Voith)	DE11	450 kW


POWER TAKEOFFS

Wide range of electronically controlled Power Take Offs for greater reliability and safety:

→ PTO on the Gearbox → Engine rear PTO

Chassis

PROFILES



WHEELBASES


2.1 M CAB		3250	3350	3500	3800	4100	4400	4700	5000	5300	5600	5900	6200	6500	6800
Rigid	4x2	•		•			•			•					
Rigid	4x4		•	•	•	•									
2.3 M CAB		3500	3700	3900	4100	4300	4500	4750	5000	5250	5500	5800	6100	6450	6800
	4x2	•	•	•	•	•	•	•		•		•			•
Rigid	6x2	•	•	•	•	•	•	•	•	•	•	•	•	•	
	6x2*4	•	•	•		•	•			•					
Tractor	4x2	•	-	•											
								_	_		_			_	_
2.3 M CAB		3200	3500	3700	3850	3900	4100	4200	4300	4500	4750	5000	5250	5500	6800
Rigid	6x4		•		•					_		•		•	

SUSPENSION

Vehicles	7,5 / 10 /12 t	12 t	13 /14 / 15 / 16 t	13 /14 / 15 / 16 t	18 / 19 / 26 t
Wheels	17.5"	19.5"	19.5"	22.5"	22.5"
Front suspension	Normal leaf spring – Reinforced leaf spring	1 3		Reinforced leaf spring	Normal leaf spring - Pneumatic
Front suspension			80 x 2000 / 825		
Rear Suspension	Normal leaf spring – Rei	nforced leaf sprin	g – Pneumatic	Reinforced leaf spring	Normal leaf spring - Pneumatic
	Lam	e normale et renf	me pour déchets : 80 x 139	6 /1000	

*With DTI 8 engine

Cab



CAB CONFIGURATIONS

Cab width		2100 mm		2300 mm	
Engine		DTI 5	DTI 8	DTI 8	DE11
	Day Cab				
	Day Cab + flat roof				
	Global Cab				
Type of cab	Crew Cab	•			
	Night & Day Cab				
Engine	Sleeper Cab			-	
	Night & Day Cab				

CAB SUSPENSION

2.1 m Cab

- → 4 elastic buffers
- 2 elastic buffers in the front of the cab and mechanical springs in the rear

2.1 m Crew Cab


- → 2 elastic buffers on the front of the cab
- 4 mechanical springs for the middle and rear of the cab


2.3 m Cab

- 4 mechanical springs
- → 4 air cushions

D (CABINE 2,1 M)


DAY CAB







CREW CAB






GLOBAL CAB





D WIDE (CABINE 2,3 M)


DAY CAB






GLOBAL CAB





SLEEPER CAB





Brakes

All of the following systems are available as standard

EBS + ASR + ESC + AEBS

EBS (Electronic Braking System)

Maintains directional control of the vehicle while avoiding wheel lock, mainly during emergency braking.

Emergency braking assistance

Braking distance optimisation during emergency stops.

Drag torque control

Maintains the vehicle's pulling power on slippery surfaces when changing down (except 4x4).

Braking harmonisation

Eliminates the feeling that the trailer is "pulling" or "pushing" during various stages of braking.

Braking warnings

- → used brake pad
- excessive brake temperature
- → reduced braking performance

Brakes and retarders activated together

Allows various braking systems to be combined: service brakes, Optibrake engine brake and other retarders.

Anti-rollover protection

Allows forward tractor rollover to be prevented when braking without a trailor.

ASR (Accelerated Skid Control)

The antiskid system maintains control of the vehicle on slippery surfaces.

ESC (Electronic Stability Control)

- → Directional stability: helps drivers maintain the rig's directional stability (particularly under difficult conditions such as rain, snow, in tight bends, etc.)
- → Anti rollover control: this function prevents rollover in critical situations such as roundabouts, tight bends or emergency directional changes.

EBL (Emergency Braking Lights)

Automatic rear stop light flashing to warn other vehicles of a dangerous situation.

Disc brake wear monitoring system

preventive maintenance (warning 20% before brakes are completely worn). Brake pad wear equalised between axles to make maintenance easier. Preventive maintenance (warning 20% before brakes are completely worn). Brake pad wear equalised between axles to make maintenance easier.

AEBS (Automatic Emergency Braking System)

Active from 15 kp/h to detect moving and stationary vehicles in front of the truck.

HSA (Hill Start Aid)*

The service brakes are held for a few seconds after releasing the pedal to make hill starts easier. This function is activated and deactivated by a push button.

*Available as an option.

Customisation

		Fixed roof deflector		
	Deflectors	Available on D 4x2 Metal aluminum speed limiter disk Adhesive speed limiter disc Twin orange revolving flashing lights Twin blue revolving flashing lights 24V kettle 25 L universal water fountain Air blower Blower connection kit Rubber mat set (1 driver, 1 passenger) Polypropylene mat set (1 driver, 1 passenger) DAB radio Independent heating kit with programming clock 22.5" stainless steel front wheel hubcap 22.5" stainless steel rear wheel hubcap		
Optimisation	Deflectors Adjustable roof deflectors Side deflectors Translucent sun visor Brown smoke tinted sun visor Antitheft Birdview 360° At cameras system with a 7" LCD screen Airbag Available on D 4x2 Metal aluminum speed limiter disk Adhesive speed limiter disc Twin orange revolving flashing lights Twin blue revolving flashing lights Twin blue revolving flashing lights Air blower Blowers Blowers Blower connection kit Rubber mat set (1 driver, 1 passenger) Polypropylene mat set (1 driver, 1 passenger) Radios DAB radio Independent heating Independent heating kit with programming clock Nuts Wheel nut cover			
		Translucent sun visor		
		Brown smoke tinted sun visor		
	Antitheft	Fuel antitheft device		
	Birdview 360°	A 4 cameras system with a 7" LCD screen		
Safety Birdwie Airbag Discs	Birdwiew front area (270°)	A 3 cameras system with a 7" LCD screen		
	Airbag	Available on D 4x2		
	Diago	Metal aluminum speed limiter disk		
	DISCS	Adhesive speed limiter disc		
	Develois a flexible a link	Twin orange revolving flashing lights		
	Discs Revolving flashing light Tw On board kitchen Blowers	Twin blue revolving flashing lights		
	On heard likehen	24V kettle		
	On board kitchen	25 L universal water fountain		
	Diaman	Air blower		
	Blowers	Blower connection kit		
Life on board		Rubber mat set (1 driver, 1 passenger)		
	Over carpet			
	Radios	DAB radio		
Antitheft Birdview 360° A 4 cam Birdwiew front area (270°) Airbag Availabl Metal al Adhesiv Twin ora Twin ora Twin blu 24V kett 25 L uni Air blow Blowers Blowers Radios Independent heating Hubcaps Nuts Personalisation Brown s Fuel ant A 4 cam A 3 cam A 4 cam A 2 cam A 2 cam A 3 cam Adhesiv Twin ora Twin blu 24V kett 25 L univ Air blow Blower or Blower or Polypropasseng Radios Independent heating University seat - ch Seat covers Made-topasseng				
	Hubana	22.5" stainless steel front wheel hubcap		
	пирсарѕ	22.5" stainless steel rear wheel hubcap		
	Nuts	Wheel nut cover		
Personalisation				
	Seat covers	passenger, front seat or tandem passenger		

Packs

PACK FUEL ECO+ VARIANTS (D, D WIDE, C 2.3)

D 2.1 - F	RTF, RTE, RTI (DTI 5, DTI 8)	CABS				
			Day	GloI	bal	
27610	Adjustable roof spoiler				•	
27806	Fixed side deflectors		•	•	l	
2VR03	Automatic engine stop after 3 minutes					
D WIDE/	/C 2.3 - RTF, RTE, RTI (DTI 8, DXi 8)		CA	BS		
		Day	Global	Night	Sleeper	
27610	Adjustable roof spoiler			•	-	
27806	Fixed side deflectors	-	-	-	•	
27602	Fixed roof spoiler		•	•	•	
2VR03	Automatic engine stop after 3 minutes					
D WIDE,	/C 2.3 - RTF, RTE, RTI (DE11)		CA	BS		
		Day	Global	Night	Sleeper	
27610	Adjustable roof spoiler				-	
27806	Fixed side deflectors	•	•	•		
27602	Fixed roof spoiler	-	-	-		
3BR02	Disengageable compressor	•	•	•	•	
2VR03	Automatic engine stop after 3 minutes		•			

PACK COMFORT VARIANTS (D)

D 2.1 - R	TF		CABS	
		Day	Global	Crew
1EL03	Leather steering wheel		•	
57584	Driver's Comfort seat with side restraint	•	•	•
80905	12 V + 24 V dashboard sockets			
88811	Overhead storage compartments with doors	•	•	•
1FF02	Storage compartment on engine tunnel	•	-	-
1FF03	Storage compartment on engine tunnel + drawer	-	•	
D 2.1 - R	TE, RTI		CABS	
		Day	Global	Crew
1EL03	Leather steering wheel		•	
57584	Driver's Comfort seat with side restraint	•	•	•
80905	12 V + 24 V dashboard sockets			
88811	Overhead storage compartments with doors	•	•	•

PACK COMFORT VARIANTS (D WIDE, C 2.3)

D WIDE/	C 2.3 - RTF		CABS		
		Day	Global	Night	Sleeper
1EL03	Leather steering wheel		•		
57584	Driver's Comfort seat with side restraint	•	•	•	•
6DR02	24 V socket in front storage compartment	-	-	-	
80905	12 V + 24 V dashboard sockets	•	•	•	•
88811	Overhead storage compartments with doors	-	•		
1FF02	Storage compartment on engine tunnel	•	-	-	-
1FF07	Rear storage compartment on engine tunnel	-	•	-	-
D WIDE/	C 2.3 - RTE, RTI		CAI	BS	
		Day	Global	Night	Sleeper
1EL03	Leather steering wheel				
57584	Driver's Comfort seat with side restraint	•	•	•	•
6DR02	24 V socket in front storage compartment	-	-	-	
80905	12 V + 24 V dashboard sockets	•	•	•	•
88811	Overhead storage compartments with doors	-	•		

PACKS SAFETY VARIANTS (D, D WIDE, C 2.3)

D 2.1 / D	WIDE / C 2.3 - RTF		CAB	
		Day	Global	Crew
18805	EBS + ASR + HSA + ESC		•	
64102	Reversing buzzer	•	•	•
74502	Fog lights		•	
77202	2 kg fire extinguisher	•	•	•
91702	1 wheel chock	•	•	
		CABS		
D 2.1 / D	WIDE / C 2.3 - RTE, RTI		CABS	
D 2.1 / D	WIDE / C 2.3 - RTE, RTI	Day	CABS Global	Crew
D 2.1 / D	WIDE / C 2.3 - RTE, RTI EBS + ASR + HSA + ESC	Day •		Crew
		Day		Crew
18805	EBS + ASR + HSA + ESC	Day		
18805 64102	EBS + ASR + HSA + ESC Reversing buzzer	Day		:







Notes

110103		

N	0	t	9	S
---	---	---	---	---

Notes

9/2023

Dimensions and specifications are provided for guidance only. The manufacturer reserves the right to change them without prior notice. Renault Trucks SAS with a capital of €50,000,000 - 954 506 077 RCS Lyon Non contractual photos









